

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 02-289311

(43)Date of publication of application : 29.11.1990

(51)Int.Cl.

B29C 33/42  
B29D 17/00  
G11B 7/26  
// B29L 17:00

(21)Application number : 01-168873

(71)Applicant : HOYA CORP

(22)Date of filing : 30.06.1989

(72)Inventor : KURIKAWA AKINORI  
KAWAI HISAO

(30)Priority



Priority number : 364 1565 Priority date : 25.01.1989 Priority country : JP

## (54) MANUFACTURE OF STAMPER AND BOARD FOR INFORMATION RECORDING MEDIUM FOR WHICH STAMPER IS USED

### (57)Abstract:

**PURPOSE:** To prevent the fringe part of a disc board from generating flashes, by a method wherein prior to or posterior to peeling of the board in a state of a flat plate, to which an already-cured resin film, to which a form of a stamping surface of a stamper is transferred, is stuck, from the stamper, an uncured part of curing resin is removed.

**CONSTITUTION:** A guide groove 9 is formed by curing an ultraviolet-curing resin film 2a by applying ultraviolet rays 8 of the outside of a treatment device 4 onto a disc board 1 for 30 seconds by transmitting through an upper plate 7 made of glass and further through the top part made of the glass of an inner chamber 5 under a state where the disc board 1 and a stamper 3 are pressure-contacted together. In addition, parts of an ultraviolet-curing resin film 2a corresponding to shading patterns 3c, 3d are not exposed and kept as it is uncured, in this curing treatment.



With this curing treatment, an already-cured part of the ultraviolet-curing resin film 2a and a disc board 1 are stuck to each other. Then since an outer circumferential surface of the disc board 1 is covered with a part of the shading pattern 3c obtained by overhanging in a state of eaves, sticking of resin to its outer circumferential surface through curing of the resin can be prevented effectively.